



Professional Amplifier

KT-P1000



Feature

- * Using Japanese ELNA audio capacitors, the sound is clear, smooth and powerful.
 - * Unparalleled singing texture, perfect vocal performance.
 - * Accurate protection circuit, more effective protection and matching of speakers.
 - * Use automatic manufacturing processes such as SMD patch and laser scanning, and imported semiconductor components, greatly improving the reliability and consistency of products.
- Designed for entertainment occasions, multimedia meetings, etc.

Specification

Model	KT-P1000
Rated power RMS(8Ω)	1000W×2
Rated power RMS(4Ω)	1500W×2
Rated power RMS (Bridged 8Ω)	3000W
Output interface	Speakon & Binding post
Frequency response	20Hz-20kHz, ±1dB
Input sensitivity	0.775V
Balanced input impedance	20KΩ (balanced) 10KΩ (unbalanced)
SNR	≥95dB
THD	≤0.03%
Isolation	>70dB (at rated output power 8 OHM 1KHz)
Damping coefficient	>240 (f=1KHz 8 OHMS)
Slew rate	15V/us
Protection mode	Soft start, short circuit protection, limit protection, DC protection, AC protection, temperature protection
Cooling system	Two-stage fan
Power supply	220-230V~50Hz
Power consumption	1000W
Product size (L×H×D)	482×88×347.7mm
Package size (L×H×D)	555×168× 430mm
Net weight	17.1Kg
Gross weight	18.6Kg