



Active Speaker

T-260H



Description

It is suitable for multimedia classrooms, general classrooms, conference rooms, training rooms, specialty stores and other places on demand of reinforcement.

Feature

- * Support 1 channel microphone, 1 channel stereo line input, 1 channel stereo line output.
- * Output overload, overvoltage, short circuit protection.
- * With mute function, the microphone has priority over the line input.
- * 1 microphone volume adjustment, 1 line input volume adjustment, 2 treble and bass adjustment.
- * Built-in HIFI high-fidelity high-end speaker and electronic crossover. Independent amplifier drive for treble and bass.
- * With 100V broadcast input interface prior to local broadcast.

Specification

Model	T-260H
Rated output power	2×25W
Output impedance	4-8Ω
Input sensitivity	AUX IN : 350mV±20mV/10KΩ ; MIC : 5mV±0.5mV
SNR	≥70dB
Frequency response	40Hz~20KHz(±3dB)
Line output	1V
Volume adjustment	1 MIC volume, 1 AUX volume
THD	≤1%
Operating temperature	5°C~40°C
Operating humidity	20% to 80% relative humidity, no condensation
Power consumption	≤60W
Supply voltage	~ 220V 50Hz
Dimension(W×H×D)mm	162×240×246
Weight	7.5kg