

GTMEDIA V8 UHD 4K TV Combo Receiver

- Multi-core CPU architecture: MIPS 74Kf core operating frequency up to 1GHz, 16KB I-cache, 16KB D-cache and 1 Register File
- Demodulation: M1502+Tuner M3031
- CPU: Ali M2662 (System:ATS)
- Flash: 64MB SPI
- DDR3: 4Gb RAM (128M*16*2)
- Connectivity: Built-in 2.4G WIFI 802.11n module, Ethernet
- Tuners: Fully comply with DVB-S/S2/S2X (SCPC and MCPC receivable from C/Ku band satellite), DVB T/T2/Cable(J83.A/B/C)/ISDBT, MPEG-2/4 H.265 Standard
- Decode: MPEG-2 ISO/IEC 13818-2 MP@ML, ISO/IEC 14496-2 (MPEG4) compliant, Supports SP@L3 to ASP@L5, Multi-format ultra-high definition video decoder (MPEG1/2/4, H.264/265, VC-1, AVS/AVS+, VP8 and VP9)
- Video Resolution: By Source, 480i, 480P, 576i, 576P, 720P_50, 720P_60, 1080i_25, 1080i_30, 1080P_25, 1080P_24, 1080P_30, 1080P_50, 1080P_60, 4K2K_25, 4K2K_30, 4K2K_50,4K2K_60
- Video DAC: 1 x 10bit DAC for CVBS output,Composite NTSC M/N/J, NTSC-4.43,Composite PAL M/N/B/D/G/H/I, PAL-60
- Aspect Mode: Auto, 16:9 Pillar box, 4:3 Pan & Scan, 4:3 Letter Box
- HDMI Video Out: Auto, RGB-Normal, RGB-Expand, YCbCr 4:4:4, YCbCr 4:2:2
- HDMI deep color: Auto, Normal, None, HDMI deepcolor 24, HDMI deepcolor 36
Panel display: 8-digit white LED display, With multiple function indicators
- USB: USB 2.0 port
- LED Indicator: Power ON: Green; Standby: Red
- IR: Exit IR for 38KHz, Infra Remote control
- Dimension: 205x80x140mm
- Weight:750g

